

Service Tools

2-3/8" - 20" Bridge Plug

The 2-3/8" through 20" are premium plugs designed to run on electric line.

Applications

Used to isolate zones for temporary or permanent abandonment.

Product Features

- Cost competitive
- Constructed with drillable materials
- Retaining rings to assist in preventing element extrusion
- Top set with shear stud
- No tension mandrel required
- Rated at 300°F
- Runs on existing electric line setting tool with most existing sleeves
- Sets in P-110 casing

Specifications Guide

Casing O.D.	T & C Weight (lbs.)	Plug O.D. (in)	Setting Range (in)		Set Force (lbs.)
			Min	Max	
2-3/8"	4.0 - 5.8	1.750	1.780	2.074	9,000
2-7/8"	6.4 - 6.5	2.220	2.340	2.525	9,000
3-1/2"	5.75 - 10.3	2.750	2.867	3.258	9,000
3-1/2"	12.8 - 15.8	2.430	2.548	2.764	9,000
4"	5.6 - 14.0	3.140	3.340	3.732	20,000
4-1/2"	9.5 - 16.6	3.562	3.826	4.090	33,000
5"	11.5 - 20.8	3.937	4.154	4.560	33,000
5-1/2"	13.0 - 23.0	4.312	4.580	5.044	33,000
5-3/4"	14.0 - 25.2	4.699	4.890	5.290	33,000
6-5/8"	17.0 - 32.0	5.375	5.595	6.135	50,000
7"	17.0 - 35.0	5.687	6.000	6.538	50,000
7-5/8"	20.0 - 39.0	6.312	6.625	7.125	50,000
8-5/8"	24.0 - 49.0	7.125	7.310	8.097	50,000
9-5/8"	29.3 - 58.4	8.125	8.435	9.063	50,000
10-3/4"	32.7 - 60.7	9.437	9.660	10.192	50,000
11-3/4"	38.0 - 60.0	10.437	10.772	11.150	50,000
11-3/4"	60.0 - 83.0	9.937	10.192	10.772	50,000
13-3/8"	48.0 - 84.5	11.880	12.175	12.715	50,000
16"	65.0 - 118	14.125	14.576	15.250	50,000
20"	94.0 - 133	18.375	18.730	19.124	50,000

