

Retrievable Packers

“G” Compression Packer

The “G” is a compression set, retrievable packer.

Applications

Most low pressure production applications. When combined with an unloader and hold down mechanism it can be used for well stimulation, testing and other pressuring operations and then left in the well as a production packer.

Features

- Rocker type slips
- Inexpensive
- J-slot control for normal set and release
- Right-hand safety joint emergency release
- Parts interchangeable with other manufacturers • Compact

Specification

Casing				Packer	
O.D.	Wt.	Min.	Max.	Max. O.D.	Standard Box x PIN
4-1/2"	9.5 - 13.5	3.910	4.160	3.771	2-3/8" EU 8RD
5"	15 - 18	4.161	4.408	4.125	2-3/8" EU 8RD
	11.5 - 15	4.408	4.560	4.250	2-3/8" EU 8RD
5-1/2"	26	4.408	4.560	4.250	2-3/8" EU 8RD
	20 - 23	4.625	4.778	4.500	2-3/8" EU 8RD
	15.5 - 20	4.778	4.950	4.641	2-3/8" EU 8RD
	13 - 15.5	4.950	5.190	4.781	2-3/8" EU 8RD
5-3/4"	22.5	4.950	5.190	4.781	2-3/8" EU 8RD
6"	26	4.950	5.190	4.781	2-3/8" EU 8RD
	20-23	5.191	5.390	5.062	2-3/8" EU 8RD
	15 - 18	5.391	5.560	5.156	2-3/8" EU 8RD
6-5/8"	34	5.561	5.595	5.406	2-3/8" EU 8RD
	28 - 32	5.596	5.791	5.484	2-3/8" EU 8RD
	24	5.830	5.921	5.656	2-7/8" EU 8RD
	17 - 20	5.922	6.135	5.812	2-7/8" EU 8RD
7"	38	5.830	5.921	5.656	2-7/8" EU 8RD
	32 - 35	5.922	6.135	5.812	2-7/8" EU 8RD
	26 - 29	6.136	6.276	5.968	2-7/8" EU 8RD
	20 - 26	6.276	6.456	6.078	2-7/8" EU 8RD
	17 - 20	6.456	6.538	6.266	2-7/8" EU 8RD
7-5/8"	33.7 - 39	6.539	6.765	6.453	2-7/8" EU 8RD
	24 - 29.7	6.766	7.025	6.672	2-7/8" EU 8RD
	20 - 24	7.025	7.125	6.812	2-7/8" EU 8RD
8-5/8"	40 - 49	7.511	7.725	7.312	3-1/2" EU 8RD
	32 - 40	7.725	7.921	7.531	3-1/2" EU 8RD
	20 - 28	7.922	8.191	7.781	3-1/2" EU 8RD
9-5/8"	47 - 53.5	8.300	8.681	8.218	4-1/2" LTC x 4-1/2" STC
	40 - 47	8.681	8.835	8.437	4-1/2" LTC x 4-1/2" STC
	29.3 - 36	8.836	9.063	8.593	4-1/2" LTC x 4-1/2" STC
10-3/4"	32.7 - 55.5	9.625	10.192	9.500	4-1/2" LTC x 4-1/2" STC

Note: Additional sizes available on request.

