

Packer Accessories

On-Off Tool

The “On-Off” Tool is a left hand release, tubing disconnect device that has an internal lock profile for securing flow control equipment.

Applications

Operations that require tubing disconnect and re-engagement without disturbing the packer. The internal lock profile is used to retain flow control devices such as plugs, valves, chokes, or regulators.

Features

- Left hand release, auto-on
- Optional right hand release
- Bonded seals allow multiple disconnects
- Can be pinned in a shear-up or shear-down position
- X, F and R Internal Lock Profiles are available
- Straight set down to engage

Specifications

—Overshot—

Tubing Size	Casing Size					
	4-1/2"	5-1/2"	7"	7-5/8"	8-5/8"	9-5/8"
2-3/8"	•	•	•			
2-7/8"		•	•	•	•	•
3-1/2"			•	•	•	•

—Seal Nipple—

Tubing Size	F - Seal Bore / X - Seal Bore						
	1.781	1.812	1.875	2.250	2.312	2.750	2.812
2-3/8"	•	•	•				
2-7/8"	•	•	•	•	•		
3-1/2"	•	•	•	•	•	•	•

—Overshot—

Tubing Size	R - Seal Bore						
	1.781	1.812	1.875	2.250	2.312	2.750	2.812
2-3/8"	•	•	•				
2-7/8"	•	•	•	•	•		
3-1/2"	•	•	•	•	•	•	•

Note: Other Seal Bores available upon request

